

PH 2600 SERIES - WMW



Characteristics

Medium Weight

Note

- Material Available in SS304, SS304L / SS316
- Clean and oil free
- Soft texture allows for easy trimming and quicker hose assembly fabrication
- Engineered for optimal hose coverage

Metric System

Item Code	DN	Braids	Braid Construction (No of Carriers X No of Strands X Wire Diameter)	Braid	 ID	 OD	 W
				Coverage			Weight
	mm			%	mm	mm	kg/m
PH2600W1R006	6	1	24 X 5 X 0.3	94	9.6	10.8	0.075
PH2600W1R008	8	1	24 X 5 X 0.3	92	12.1	13.6	0.090
PH2600W1R010	10	1	24 X 6 X 0.3	92	14.1	15.7	0.120
PH2600W1R012	12	1	24 X 8 X 0.3	92	16.7	18.2	0.140
PH2600W1R016	16	1	36 X 7 X 0.3	96	21.9	23.5	0.190
PH2600W1R020	20	1	36 X 9 X 0.3	94	26.7	28.2	0.255
PH2600W1R025	25	1	36 X 10 X 0.3	96	32.3	33.8	0.260
PH2600W1R032	32	1	48 X 8 X 0.4	94	41.2	43.0	0.504
PH2600W1R040	40	1	48 X 9 X 0.4	92	49.5	51.3	0.580
PH2600W1R050	50	1	48 X 10 X 0.4	96	60.7	62.6	0.630
PH2600W1R065	65	1	72 X 7 X 0.5	95	78.3	80.3	1.030
PH2600W1R080	80	1	72 X 8 X 0.5	93	96.5	98.5	1.195
PH2600W1R100	100	1	72 X 10 X 0.5	88	116.2	118.2	1.471
PH2600W1R125	125	1	72 X 10 X 0.6	92	149.0	152.5	2.100
PH2600W1R150	150	1	72 X 11 X 0.6	90	176.0	178.0	2.300
PH2600W1R200	200	1	96 X 10 X 0.6	90	228.0	236.0	3.300
PH2600W1R250	250	1	96 X 12 X 0.6	90	278.0	285.0	4.100
PH2600W1R300	300	1	96 X 12 X 0.7	94	334.0	336.0	6.400

Imperial System

Item Code	DN	Braids	Braid Construction (No of Carriers X No of Strands X Wire Diameter)	Braid	 ID	 OD	 W
				Coverage			Weight
	inch			%	inch	inch	lbs/ft
PH2600W1R006	1/4	1	24 X 5 X 0.012	94	0.4	0.4	0.050
PH2600W1R008	5/16	1	24 X 5 X 0.012	92	0.5	0.5	0.060
PH2600W1R010	3/8	1	24 X 6 X 0.012	92	0.6	0.6	0.080
PH2600W1R012	1/2	1	24 X 8 X 0.012	92	0.7	0.7	0.094
PH2600W1R016	5/8	1	36 X 7 X 0.012	96	21.9	23.5	0.128
PH2600W1R020	3/4	1	36 X 9 X 0.012	94	26.7	28.2	0.171

Item Code	DN	Braids	Braid Construction (No of Carriers X No of Strands X Wire Diameter)	Braid	 ID	 OD	 W
				Coverage			Weight
	inch			%	inch	inch	lbs/ft
PH2600W1R025	1	1	36 X 10 X 0.012	96	32.3	33.8	0.175
PH2600W1R032	1.1/4	1	48 X 8 X 0.016	94	41.2	43.0	0.339
PH2600W1R040	1.1/2	1	48 X 9 X 0.016	92	49.5	51.3	0.390
PH2600W1R050	2	1	48 X 10 X 0.016	96	60.7	62.6	0.423
PH2600W1R065	2.1/2	1	72 X 7 X 0.02	95	78.3	80.3	0.692
PH2600W1R080	3	1	72 X 8 X 0.02	93	96.5	98.5	0.803
PH2600W1R100	4	1	72 X 10 X 0.02	88	116.2	118.2	0.988
PH2600W1R125	5	1	72 X 10 X 0.024	92	149.0	152.5	1.411
PH2600W1R150	6	1	72 X 11 X 0.024	90	176.0	178.0	1.546
PH2600W1R200	8	1	96 X 10 X 0.024	90	228.0	236.0	2.217
PH2600W1R250	10	1	96 X 12 X 0.024	90	278.0	285.0	2.755
PH2600W1R300	12	1	96 X 12 X 0.028	94	334.0	336.0	4.300