

PH280 - WATER BLAST 30



Construction

Inner tube	Black colour, Synthetic rubber resistant to oil and water
Reinforcement	Four high tensile steel wire spirals
Cover	Black colour, Synthetic rubber resistant to abrasion and weather, oil & ozone
Application	Water blasting, Water jetting, cleaning equipment. Delivery of water and water emulsions

Cover Options

PH280 : MSHA

Item Code	Dash Size	DN	ID		RI OD		OD		WP		BP		BR/r		W kg/m
			inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	
PH280-04	-04	06	1/4	6.4	0.58	14.7	0.70	17.9	12325	850	30815	2125	5.12	130	0.627
PH280-06	-06	10	3/8	9.5	0.69	17.5	0.83	21.1	12325	850	30815	2125	6.10	155	0.838
PH280-08	-08	12	1/2	12.7	0.84	21.3	0.97	24.6	12325	850	30815	2125	7.87	200	1.184
PH280-12	-12	19	3/4	19.0	1.17	29.8	1.29	32.8	12325	850	30815	2125	9.84	250	2.024
PH280-16	-16	25	1	25.4	1.38	35.1	1.51	38.3	12325	850	30815	2125	11.81	300	2.447



Temperature Range : Continuous: -40°C to +90°C