

PH301 - SEWER JET - 2500 PSI



Construction

Inner tube	Thermoplastic Elastomer
Reinforcement	One or more Braids of Synthetic Fiber
Cover	Polyurethane, Orange Colour
Application	Standard Sewer cleaning vehicles and cleaning equipments. Special construction for optimum cut and wear resistance with bonded tube and cover. Available in long lengths with a special cover resistant to microbiological degradation light weight compared to Conventional rubber alternatives and increased lifetime

Note : Special colours available on request

Item Code	Dash Size	DN	ID		OD		WP		BP		BR/r		W W
			inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	
PH301-03	-03	05	3/16	4.8	0.413	10.5	2500	175	6250	438	1.6	40	83
PH301-04	-04	06	1/4	6.4	0.505	12.8	2500	175	6250	438	1.6	40	118
PH301-06	-06	10	3/8	9.5	0.640	16.3	2500	175	6250	438	2.4	60	167
PH301-08	-08	12	1/2	12.7	0.810	20.6	2500	175	6250	438	4.0	100	248
PH301-10	-10	16	5/8	16.0	1.030	26.2	2500	175	6250	438	4.3	110	417
PH301-12	-12	20	3/4	19.0	1.150	29.2	2500	175	6250	438	5.0	125	496
PH301-16	-16	25	1	25.4	1.450	36.8	2500	175	6250	438	6.3	160	714
PH301-20	-20	32	1.1/4	31.8	1.800	45.7	2500	175	6250	438	10.0	250	1106



Temperature Range : Continuous: -40°C to +60°C